

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: CLEARGARD EPOXY - PART A
PRODUCT CODE: 47-424 CLEAR

HMIS CODES: H F R P
1*1 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: NELSONITE POOL AND DECK COATING
ADDRESS : 3150 E. PICO BLVD.
LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 11/4/2011
INFORMATION PHONE : (323) 261-8114 NAME OF PREPARER :

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mmHG @TEMP(F)
EPOXY RESIN OSHA PEL: NE, ACGIH TLV: NE	25085-99-8	0 68

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): n/a	DENSITY: 8.92 lb/gl
VAPOR DENSITY: HEAVIER THAN AIR	SPECIFIC GRAVITY (H2O=1): 1.07
COATING V.O.C.: 0.58 lb/gl	MATERIAL V.O.C.: 0.27 lb/gl
COATING V.O.C.: 69 g/l	MATERIAL V.O.C.: 33 g/l
SOLUBILITY IN WATER: Miscible	EVAPORATION RATE: SLOWER THAN ETHER
APPEARANCE AND ODOR: Milky liquid with a slight odor.	

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): >200 METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: n/a UPPER: n/a

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Do not enter fire area without proper protection. Fight fire from safe distance location. Heat may build pressure closed containers, spreading fire, increasing risk of burns. Notify authorities if liquid enters sewer/public waters.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may rupture due to buildup of steam pressure when exposed to extreme heat such as fire.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Sparks, flames, excessive heat, poor ventilation

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents, strong Lewis or mineral acids, and strong mineral and organic bases, especially primary and secondary aliphatic amines.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause respiratory tract irritation and sensitization. High levels of exposure may cause red blood cell damage.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May be severely irritating to the eyes and cause corneal damage. Prolonged or repeated contact with skin may cause de-fatting and drying, resulting in irritation and dermatitis.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May penetrate skin. Frequent or widespread contact may result in the absorption of potentially harmful amounts, which can cause damage to red blood cells.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May be harmful if swallowed. Material is moderately toxic and may cause damage to red blood cells.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye, nose and skin irritation, headache, nausea and vomiting.
Chronic: Long term exposure may lead to skin sensitization (dermatitis) and damage to red blood cells and blood forming organs.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: MOVE PERSON TO FRESH AIR. EYE & SKIN CONTACT: FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. WASH AFFECTED AREAS WITH SOAP AND WATER IMMEDIATELY. REMOVE CONTAMINATED CLOTHING. INGESTION: IF SWALLOWED, DILUTE BY DRINKING 2 GLASSES OF WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ABSORB WITH INERT MATERIAL (SAND, VERMICULITE, ETC.), SWEEP OR SCOOP UP AND PUT IN DISPOSAL CONTAINER. FLUSH AREA OF SPILL WITH WATER.

WASTE DISPOSAL METHOD

Incinerate or dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid contact with eyes, skin or clothing. Avoid breathing mist or vapor. Do not swallow. Wash thoroughly after handling. Do not eat, drink or smoke in work areas. Keep container closed when not in use. Use only with adequate ventilation. Store in a cool, dry, well-ventilated area.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact.

===== SECTION VIII - CONTROL MEASURES =====

VENTILATION

Local exhaust at point of use in closed spaces.

RESPIRATORY PROTECTION

None required in out-of-doors. Maintain good ventilation in closed spaces.

PROTECTIVE GLOVES

Impermeable chemical handling gloves for skin protection.

EYE PROTECTION

Safety glasses with side shields or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - TRANSPORT INFORMATION =====

DOT (GROUND)

Not regulated

AIR

Not regulated

===== SECTION X - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

None

===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, NELSONITE POOL AND DECK COATING makes no warranty expressed or implied regarding the accuracy of these data or the

results to be obtained from the use thereof. NELSONITE POOL AND DECK COATING assumes no responsibility for injury from the use of the product described herein.