

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: W/PROOFING CONC.& MASONRY SEAL.TINT BASE
 PRODUCT CODE: 47-700T

HMIS CODES: H F R P
 2*1 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: NELSONITE POOL AND DECK COATING
 ADDRESS : 3150 E. PICO BLVD.

LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 10/23/06
 INFORMATION PHONE : (800) 544-1998 NAME OF PREPARER : N/A

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mmHG	@TEMP(F)	WEIGHT PERCENT
TITANIUM DIOXIDE (as total nuisance dust) OSHA PEL: 10 ppm, ACGIH TLV: 10 mg/m3	13463-67-7	NA	NA	13
~ DIETHYLENE GLYCOL MONOMETHYL ETHER OSHA PEL: N/E, ACGIH TLV: N/E	111-77-3	.1	68	4.57
BUTYL BENZYL PHTHALATE	85-68-7	.16	302	1.4
~ AMMONIUM HYDROXIDE ACGIH TLV: 25 ppm	1336-21-6	420	60	0.53

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 195 - 450 DENSITY: 9.93 lb/gl
 VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 1.19
 COATING V.O.C.: 2.02 lb/gl MATERIAL V.O.C.: 0.74 lb/gl
 COATING V.O.C.: 242 g/l MATERIAL V.O.C.: 89 g/l
 SOLUBILITY IN WATER: Soluble EVAPORATION RATE: SLOWER THAN ETHER
 APPEARANCE AND ODOR: White liquid with mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): >200 METHOD USED: TCC
 FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: .26 UPPER: n/a

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Use approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Material will not sustain combustion unless water has evaporated. Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Excessive heat and open flames

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizers

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: Concentrated vapors may be harmful. May cause headache, dizziness and nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin and eye contact: May cause irritation to both.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May cause irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: Maybe harmful if swallowed.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye and skin irritation, nausea, headache and dizziness.

Chronic: May cause liver abnormalities, kidney damage, lung damage, blood abnormalities, spleen damage and testis damage.

CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED: Yes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PROVIDE VENTILATION. LARGE SPILLS MAY BE SCOOPED UP. SMALL SPILLS MAY BE PICKED UP WITH ABSORBENT MATERIALS.

WASTE DISPOSAL METHOD

Place in tightly closed containers. Incinerate or dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store away from high temperatures, sparks and open flame. Keep containers tightly closed.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact with skin.

===== SECTION VIII - CONTROL MEASURES =====

VENTILATION

Adequate volume and pattern to keep air contaminant concentration below current applicable OSHA or ACGIH's TLV limits.

RESPIRATORY PROTECTION

In case of poor ventilation, use approved organic vapor mask.

PROTECTIVE GLOVES
Chemical resistant gloves

EYE PROTECTION
Chemical goggles, safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
Eye bath and safety shower

WORK/HYGIENIC PRACTICES
Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Contains: Butyl Benzyl Phthalate(BBP) -

===== SECTION X - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, NELSONITE POOL AND DECK COATING makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. NELSONITE POOL AND DECK COATING assumes no responsibility for injury from the use of the product described herein.